

**SURFACE MOUNT LL-34
SWITCHING DIODE**

FEATURES


- * Fast Switching Device($T_{RR}<4.0nS$)
- * LL-34 Glass Case
- * Through-Hole Device Type Mounting
- * Hermetically Sealed Glass
- * Compression Bonded Construction
- * All external surfaces are corrosion resistant and leads are readily solderable

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



LL-34



Absolute Maximum Ratings (Ta=25 °C)

	Symbol	Value	UNIT
Reverse Voltage	V_R	75	V
Reverse Recovery Time $I_F=-I_R=10mA$ to $I_{RR}=-1mA$ $V_R=6V$ $R_L=100$ ohms	trr	4	ns
Power Dissipation at Tamb= 25°C 3.33mW/°C	P_{tot}	500	mW
Forward Current	I_F	300	mA
Junction Temperature	T_j	175	°C
Storage Temperature Range	T_S	-65 to +175	°C

Electrical Characteristics (Ta=25 °C)

	Symbol	Min	Max	Unit
Minimum Breakdown Voltage @ $I_R = 100\mu A$	BV	100	-	V
Rectifier Current (Average) Half Wave Rectification w/Resist Load at Ta= 25 °C and f > or = 50Hz	I_O	-	500	mA
Peak Forward Surge Current PW<1 sec	I_{Fsurge}	-	500	mA
Maximum Forward Voltage IF = 10 mA	V_F	-	1.0	V
Maximum reverse Leakage Current at $V_R = 20V$ at $V_R = 75V$ at $V_R = 20V, T_J = 150^\circ C$	I_R	- - -	0.025 5.0 50	μA
Maximum Junction Capacitance $V_F = V_R = 0, f = 1MHz$	C_j	-	4	pF
Reverse Recovery Time From $I_F = -I_R = 10mA$ to $I_{RR} = -1mA$ $V_R = 6V, R_L = 100$ ohms	trr	-	4	ns
Maximum Thermal Resistance Junction to Ambient Air	R_{thJA}	-	0.35	$^\circ C/mW$
Rectification Efficiency at f=100MHZ, $V_{rf} = 2V$	nv	0.45	-	-

PACKAGING OF DIODE AND BRIDGE RECTIFIERS

REEL PACK

PACKAGE	PACKING CODE	EA PER REEL	EA PER INNER BOX	COMPONENT SPACE (mm)	TAPE SPACE (mm)	REEL DIA (mm)	CARTON SIZE (mm)	EA PER CARTON	GROSS WEIGHT(Kg)
LL-34	-T	2,500	-----	----	----	178	390*205*310	100,000	8.40

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.