Senseair S8 Residential

A very small, versatile and mass-producible CO₂ sensor module

More than 30 years experience of research and development within the field of infrared gas sensing has brought us our smallest NDIR CO₂ sensor. The sensor has excellent performance such as high accuracy and low power consumption.

Senseair S8 Residential is designed for high volume production with full traceability by sensor serial number on all manufacturing processes and key components. Every sensor is individually calibrated and is provided with UART digital interface. The sensor is maintenancefree and has an estimated life time of more than 15 years.

Senseair S8 Residential is a module that is designed for simple integration into products. Senseair S8 Residential can be used in a wide range of applications such as ventilation control to improve energy savings and to assure a good indoor climate. Other fields of use are personal safety and measurements to increase process yield and to increase economic value in bio-related processes.



Standard specification

Measured gas Operating principle

Measurement range CO₂ Accuracy CO Maintenance Life expectancy Power supply Operation temperature range Communication Dimensions Energy consumption

Response time

Carbon dioxide (CO_o) Non-dispersive infrared (NDIR) 400 - 2000 ppm ±70 ppm ±3% of reading^{1,2} No maintenance required >15 years 4.5 - 5.25 V DC 0 - 50 °C UART (Modbus) 33.9 x 19.8 x 8.7 mm 300 mA peak 30 mA average 2 minutes by 90%

Key benefits

- Miniature size
- Individually calibrated
- Maintenance-free
- Long term stability
- Low power consumption







Note 1: In normal IAQ applications. Accuracy is defined after minimum three (3) ABC periods of continuous operation with ABC on.

Note 2: Accuracy is specified over operating temperature range. Specification is referenced to certified calibration mixtures. Uncertainty of calibration gas mixtures (±1% currently) is to be added to the specified accuracy for absolute measurements.