

High Frequency Chip Resistors



■RFD series

Features

- A resistor that takes advantage of the characteristics of thin films, and supports a wide range of frequencies from DC to 30 GHz.
- Small 0603 size
- Face-down mounting type



Applications

- Low noise high frequency transmission and reception circuit
- High frequency termination circuit
- High frequency attenuation circuit

◆Part numbering system

RFD 0603 P - 50R0 - D - T1

Series code

Size:0603

TCR P: $\pm 25\text{ppm}$

Packaging quantity:
T5(5,000pcs), T1(1,000pcs)


Resistance tolerance D : $\pm 0.5\%$, M $\pm 20\%$

Resistance values : 50Ω

◆Electrical Specification

| Type | RFD0603 |
|-----------------------------|---|
| Impedance | 50Ω |
| Operating frequency | DC~30GHz |
| rated power | 50mW |
| Rated operating temperature | 70°C |
| Operating temperature | -40°C~+125°C |
| Packaging quantity | 1,000pcs/reel(T1) 5,000pcs/reel(T5) 10,000pcs./reel (T10) |


◆Dimensions




| Type (mm) | Size (inch) | L | W | t | a | b |
|-----------|-------------|-----------------|-----------------|----------|-----------------|-----------------|
| RFD0603 | 0201 | 0.60 ± 0.05 | 0.30 ± 0.05 | max 0.30 | 0.30 ± 0.05 | 0.14 ± 0.05 |

(unit : mm)

◆ Recommended land patterns(soldering footprints)



◆ Derating Curve



◆ High frequency characteristics

