

Temperature and humidity regulator with 230Vac/8A relays

code: H3061



Humidistat, thermostat with two relay outputs. Outdoor, indoor use. Relative humidity, temperature probe on a cable. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio, specific enthalpy.

The device is supplied with T+RH probe with 1 meter cable.

Technical data

TEMPERATURE SENSOR	
Measuring range	-30 to +105 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	±2.5 % RH from 5 to 95 % at 23 °C
Resolution	0.1% RH
DEW POINT	
Measuring range	-60 to +80 °C
Accuracy	±1.5 °C at ambient temperature T <25 °C and RH >30 %
Resolution	0.1 °C
RELAY OUTPUTS	
Quantity	2
Maximal voltage	250 VAC
Maximal current	8 A
Maximal power	2000 VA AC, 192 W DC
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +80 °C
Channels	1x connectable temperature+humidity probe
Counted values	dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy
Acoustic alarm	from built-in beeper - switchable
Power	110-240 VAC
Protection class	IP65 electronics; IP40 sensors
Dimensions	136 x 161 x 45 mm; length/diameter of external probe 88/18 mm
External probe cable length	1 meter
Weight	approx. 450 g

Warranty	3 years
----------	---------