



vPolyTan™ FAMILY OF PRODUCTS

Tantalum Capacitors

	CASE SIZE		KEY RATINGS (ESR, mΩ)	MARKET SEGMENT
T58 General Purpose	MM 1608-09		10 μF-6.3 V (300) 22 μF-6.3 V (300)	Smartphones, Tablets, Ultra-thin Notebooks
	M0 1608-10		33 μF-6.3 V (300) 47 μF-6.3 V (300)	
	W9 2012-09		47 μF-6.3 V (150)	
	A0 3216-10		100 μF-6.3 V (100) 47 μF-10 V (100)	Industrial
	BB 3528-20		330 μF-6.3 V (50) 220 μF-10 V (50) 47 μF-16 V (90) 22 μF-25 V (90)	
T59 Ultra-Low ESR	EE 7343-40		220 μF-16 V (25) 330 μF-16 V (25) 470 μF-16 V (25)	Solid-State Drives (SSD) Network Infrastructure Equipment
T54 Ultra-Low ESR High-Reliability COTS	EE 7343-40		220 μF-16 V (25) 330 μF-16 V (25) 100 μF-25 V (60) 150 μF-30 V (150) 47 μF-35 V (100) 22 μF-50 V (75)	Avionics, Military, Space
T52 High Capacitance Low Profile	M1 7360-20		1500 μF-6.3 V (25)	Solid-State Drives (SSD)