



CONFIDENTIAL & PROPRIETARY INFORMATION

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM (INCH)



NOTES:

- MAGNET PROPERTIES PER N-35SH:
 Br: 11,800-12,200 G
 Hc: 10,800-11,500 Oe
 Hci: ≥20,000 Oe
 T max: 150 C
- SUPPLIED MAGNETIZED THROUGH THE DIAMETER
- PARTS ARE NICKEL PLATED FOR 15 HRS SALT SPRAY MIN.



| REV | DESCRIPTION | DATE | BY |
|-----|-------------|------|----|
| | | | |
| | | | |
| | | | |
| | | | |

TOLERANCES
(UNLESS OTHERWISE NOTED)

DECIMAL METRIC
 X.XX = ± .01 X.X = ± .25
 X.XXX = ± .005 X.XX = ± .13

ANGLES
 ± .5°

DO NOT SCALE DRAWING

| | | |
|---|-------------|----------------------|
| Alliance LLC | | |
| 1450 CLARK DRIVE, VALPARAISO, INDIANA 46385 | | |
| DESCRIPTION: 4 mm x 4 mm DISC MAGNET | | |
| SENSOR MAGNET | | P/N: ALC4040D |
| GRADE: N-35SH | Drwg by: BT | REV LEVEL: A |
| COATING: Nickel | Appr by: DV | Approval: 06-15-2017 |