

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

1t1578is8-2.5#pbf

(Engineering Calculation)

SOIC

(printed on: 2020-07-11 17:31:22)

**TOTAL MASS (g) : 0.075425**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.003570	1000000	47331.8789062		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.023653	975000	313596.9375		
		Iron (Fe)	7439-89-6	0.000582	24000	7716.28955078		
		Phosphorus (P)	7723-14-0	0.000007	300	92.8076095581		
		Zinc (Zn)	7440-66-6	0.000017	700	225.389907837		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.024259</b>	<b>1000000</b>	<b>321631.40625</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.001477	1000000	19580.4433594		
		<b>External Plating Total:</b>				<b>0.001477</b>	<b>1000000</b>	<b>19580.4433594</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000194	1000000	2572.09643555		
		<b>Internal Plating Total:</b>				<b>0.000194</b>	<b>1000000</b>	<b>2572.09643555</b>
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.001019	750000	13510.1357422		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000340	250000	4507.79833984		
<b>Die Attach Total:</b>				<b>0.001359</b>	<b>1000000</b>	<b>18017.9355469</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.006657	150000	88260.0390625		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.036392	820000	482493.5		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.001110	25000	14716.6347656		
		Carbon Black (C)	1333-86-4	0.000222	5000	2943.3269043		
		<b>Encapsulation Total:</b>				<b>0.044381</b>	<b>1000000</b>	<b>588413.5</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000185	1000000	2452.77246094		
					<b>TOTAL MASS (g) :</b>	<b>0.075425</b>		