



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-----------------|
| L | 14.2mm MAX |
| W | 9.2mm MAX |
| H | 5.4mm MAX |
| LL | 2.8mm +/-0.1mm |
| S | 7.62mm +/-0.2mm |
| S1 | 2.54mm +/-0.2mm |
| F | 0.5mm +/-0.1mm |
| F1 | 0.25mm +/-0.1mm |

Packaging Specifications

| | |
|-----------|------|
| Packaging | Bulk |
|-----------|------|

General Information

| | |
|-------------|--|
| Series | EA2 |
| Style | Through-Hole |
| Description | Miniature Signal Relay, Non-latch |
| Features | Compact Size, Flat-Package. FCC (1500 V) surge capacity. UL recognized and CSA certified. Low power consumption (100-200 mW) |
| RoHS | Yes |
| Coil Type | Single Coil (Non-Latching) |

Specifications

| | |
|-------------------------|---|
| Temperature Range | -40/+85°C |
| Coil Voltage | 12 V |
| Coil Resistance | 1028 Ohms +/-10% |
| Contact Form | 2 Form C (DPDT) |
| Contact Material | Silver Alloy With Gold Alloy Overlay |
| Voltage Characteristics | 9 (Operate) / 1.2 (Release) |
| Switching Power | 30 W, 62.5 VA |
| Switching Voltage DC | 220 V |
| Switching Voltage AC | 250 VAC |
| Switching Current | 1 A |
| Contact Current Class | >10A |
| Carrying Current | 2 Amps |
| Contact Resistance | 75 mOhms |
| Operation Time | Approximately 2ms |
| Release Time | Approximately 1ms |
| Insulation Resistance | 1 GOhms |
| Withstanding Voltage | 1000 VAC (1min) 1500 V Surge |
| Miscellaneous | Not Available, Please Contact MFG for other options |