







<b>Product / Process Change Notification (PCN)</b>	
<input checked="" type="checkbox"/> Major change <input type="checkbox"/> Minor change	
<b>PCN #:</b> PCN_IndPDW_20230225  <b>Affected Series:</b> WE-PD; 744770xxxW, 744771xxxW, 744778xxxW, 744777xxxW  <b>PCN Date:</b> November 25, 2022  <b>Effective Date:</b> February 25, 2023	<b>Change Category:</b> <input type="checkbox"/> Equipment / Location <input type="checkbox"/> General Data <input checked="" type="checkbox"/> Material <input type="checkbox"/> Process <input type="checkbox"/> Product Design <input type="checkbox"/> Shipping / Packaging <input type="checkbox"/> Supplier <input type="checkbox"/> Software
<b>Contact:</b> Product Management  <b>Phone:</b> +49 (0) 7942 - 945 5001  <b>Fax:</b> +49 (0) 7942 - 945 5179  <b>E-Mail:</b> pcn.eisos@we-online.com	<b>Data Sheet Change:</b> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No  <b>Attachment:</b> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
<b>Description and purpose of change:</b> Due to external influences, Würth Elektronik releases a new coating for core and ring of the component. All products with date code 2022-12-01 or later, will be affected by this change. There will be no change in fit, function, quality or reliability of the product.	
<b>Detail of Change:</b> Due to external influences, the current coating used for the WE-PDW is not available anymore. To ensure the constant availability of the product, a new coating for core and ring has been released for the WE-PDW.	

Appearance Before Change	Appearance After Change
<p data-bbox="181 412 293 439"><b>Size 12xx</b></p>  <p data-bbox="181 1016 293 1043"><b>Size 73xx</b></p> 	<p data-bbox="829 412 941 439"><b>Size 12xx</b></p>  <p data-bbox="829 1016 941 1043"><b>Size 73xx</b></p> 
<p data-bbox="165 1478 580 1505"><b>Reliability / Qualification Summary:</b></p> <p data-bbox="165 1518 316 1545">Qualification:</p> <ul data-bbox="165 1559 766 1666" style="list-style-type: none"><li>- External Visual MIL-STD-883 Method 2009</li><li>- Physical Dimensions JESD22 Method JB-100</li><li>- Resistance to Solder Heat J-STD-020</li></ul>	