

Features

- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Low Forward Voltage Drop
- Lead Free Finish/Rohs Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +125°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance :667°C/W Junction to Ambient

Parameter	Symbol	Rating	Units
Peak Repetitive Reverse Voltage	V_{RRM}	40	Vdc
Working Peak Reverse Voltage	V_{RWM}	40	Vdc
RMS Reverse Voltage	$V_{R(RMS)}$	28	Vdc
Average Rectified Output Current	I_O	1.5	Adc
Peak Forward Surge Current @t<8.3ms	I_{FSM}	8.0	Adc
Power Dissipation	P_d	150	mW

Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Symbol	Min	Typ	Max	Units
Reverse Breakdown Voltage ($I_R=250\mu A$)	$V_{(BR)}$	40	---	---	Vdc
Forward Voltage ($I_F=0.5Adc$)	V_F	---	---	0.40	Vdc
($I_F=1.0Adc$)		---	---	0.45	
($I_F=1.5Adc$)		---	---	0.58	
Reverse Current ($V_R=20Vdc$)	I_R	---	---	40	μA dc
($V_R=40Vdc$)		---	---	50	
Diode Capacitance ($V_R=0Vdc, f=1MHz$)	C_T	---	180	---	pF


Device Marking: BD

Internal Structure:



**1.5 A
Schottky Barrier
Rectifier
40 Volts**


FBP-02L



DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.018	0.022	0.45	0.55	
B	0.000	0.004	0.01	0.09	
C	0.033REF.		0.850REF.		
D	0.030	0.033	0.75	0.85	
E	0.061	0.065	1.55	1.65	
F	0.016 REF.		0.410 REF.		
G	0.003 REF.		0.080 REF.		
H	0.013 REF.		0.340 REF.		
J	0.024	0.030	0.60	0.76	
K	0.020	0.027	0.52	0.68	
L	0.035	0.039	0.90	1.00	

Suggested Solder Pad Layout



Curve Characteristics

Fig. 1 - Forward Characteristics




Fig. 2 - Reverse Characteristics




Fig. 3 - Capacitance Characteristics





Fig. 4 - Power Derating Curve



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel:10Kpcs/Reel

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.