



Micro Commercial Components



Micro Commercial Components  
 130 W Cochran St, Unit B  
 Simi Valley, CA 93065  
 USA  
 Tel:818-701-4933

**MT130C08T2**  
**MT130C12T2**  
**MT130C16T2**  
**MT130C18T2**


**130 Amp**  
**THYRISTOR MODULE**  
**800~1800 Volts**

## Features

- Lead Free Finish/RoHS Compliant (NOTE 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- International standard package
- Heat transfer through aluminum oxide DBC ceramic isolated metal baseplate
- Glass passivated chip
- Simple Mounting


## Applications

- Power Converters
- Lighting Control
- DC Motor Control and Drives
- Heat and temperature control



| DIM | INCHES     |       | MM      |       | NOTE |
|-----|------------|-------|---------|-------|------|
|     | MIN        | MAX   | MIN     | MAX   |      |
| A   | 0.894      | 0.917 | 22.50   | 23.50 |      |
| B   | 1.169      | 1.193 | 29.50   | 30.50 |      |
| C   | 0.343      | 0.366 | 8.50    | 9.50  |      |
| D   | 0.323      | 0.343 | 8.00    | 8.90  |      |
| E   | 1.051      | 1.075 | 26.50   | 27.50 |      |
| F   | 1.130      | 1.154 | 28.50   | 29.50 |      |
| G   | 0.120      | 0.130 | 79.50   | 80.50 |      |
| H   | 0.500      | 0.524 | 12.50   | 13.50 |      |
| I   | 2.501      | 2.531 | 63.50   | 64.50 |      |
| J   | 3.689      | 3.713 | 93.50   | 94.50 |      |
| K   | 0.256      |       | 6.50    |       | ∅    |
| L   | 0.500      | 0.524 | 12.50   | 13.50 |      |
| M   | 1.327      | 1.350 | 33.50   | 34.50 |      |
| N   | 0.032X0.11 |       | 0.8X2.8 |       |      |
| O   | 0.677      | 0.700 | 17.00   | 18.00 |      |
| P   | 0.185      | 0.209 | 4.50    | 5.50  |      |
| Q   | 0.185      | 0.209 | 4.50    | 5.50  |      |
| R   | 0.902      | 0.925 | 22.70   | 23.70 |      |

**Circuit**



## Module Type

| TYPE       | VRRM  | VSRM  |
|------------|-------|-------|
| MT130C08T2 | 800V  | 900V  |
| MT130C12T2 | 1200V | 1300V |
| MT130C16T2 | 1600V | 1700V |
| MT130C18T2 | 1800V | 1900V |

## Maximum Ratings

| Symbol    | Conditions  | Values       | Units            |
|-----------|---|--------------|------------------|
| $I_{TAV}$ | Sine 180°; $T_c=85^\circ\text{C}$   | 130          | A                |
| $I_{TSM}$ | $T_{VJ}=45^\circ\text{C}$ t=10ms, sine  | 4700         | A                |
|           | $T_{VJ}=125^\circ\text{C}$ t=10ms, sine   | 4000         |                  |
| $i^2t$    | $T_{VJ}=45^\circ\text{C}$ t=10ms, sine  | 110000       | A2s              |
|           | $T_{VJ}=125^\circ\text{C}$ t=10ms, sine   | 80000        |                  |
| Visol     | a.c.50HZ;r.m.s.;1min  | 3000         | V                |
| $T_{vj}$  |   | -40 to 130   | $^\circ\text{C}$ |
| $T_{stg}$ |   | -40 to 125   | $^\circ\text{C}$ |
| $M_t$     | To terminals(M6)  | $3 \pm 15\%$ | Nm               |
| $M_s$     | To heatsink(M6)   | $5 \pm 15\%$ | Nm               |
| di/dt     | $T_{VJ}=T_{VJM}$ , $2/3V_{DRM}$ , $I_G=500\text{mA}$<br>$Tr<0.5\mu\text{s}$ , $tp>6\mu\text{s}$ | 200          | A/ $\mu\text{s}$ |
| dv/dt     | $T_J=T_{VJM}$ , $2/3V_{DRM}$ , linear voltage rise  | 1000         | V/ $\mu\text{s}$ |
| a         | Maximum allowable acceleration  | 50           | $\text{m/s}^2$   |
| Weight    | Module(Approximately)   | 165          | g                |


## Thermal Characteristics

| Symbol        | Conditions                       | Values    | Units              |
|---------------|----------------------------------|-----------|--------------------|
| $R_{th(j-c)}$ | Cont.;per thyristor / per module | 0.18/0.09 | $^\circ\text{C/W}$ |
| $R_{th(c-s)}$ | per thyristor / per module       | 0.1/0.05  | $^\circ\text{C/W}$ |


## Electrical Characteristics

| Symbol            | Conditions  | Values |      |      | Units            |
|-------------------|---|--------|------|------|------------------|
|                   |   |        |      |      |                  |
| $V_{TM}$          | $T=25^\circ\text{C}$ $I_{TM}=500\text{A}$                                     |        |      | 1.8  | V                |
| $I_{RRM}/I_{DRM}$ | $T_{VJ}=T_{VJM}$ , $V_R=V_{RRM}$ , $V_D=V_{DRM}$                              |        |      | 40   | mA               |
| $V_{TO}$          | For power-loss calculations only ( $T_{VJ}=125^\circ\text{C}$ )               |        |      | 1    | V                |
| $r_T$             | $T_{VJ}=T_{VJM}$  |        |      | 1.6  | $\text{m}\Omega$ |
| $V_{GT}$          | $T_{VJ}=25^\circ\text{C}$ , $V_D=6\text{V}$                                   |        |      | 3    | V                |
| $I_{GT}$          | $T_{VJ}=25^\circ\text{C}$ , $V_D=6\text{V}$                                   |        |      | 150  | mA               |
| $V_{GD}$          | $T_{VJ}=125^\circ\text{C}$ , $V_D=2/3V_{DRM}$                                 |        |      | 0.25 | V                |
| $I_{GD}$          | $T_{VJ}=125^\circ\text{C}$ , $V_D=2/3V_{DRM}$                                 |        |      | 10   | mA               |
| $I_L$             | $T_{VJ}=25^\circ\text{C}$ , $R_G=33\Omega$                                    | 300    | 1000 |      | mA               |
| $I_H$             | $T_{VJ}=25^\circ\text{C}$ , $V_D=6\text{V}$                                   | 150    | 400  |      | mA               |
| tg $d$            | $T_{VJ}=25^\circ\text{C}$ , $I_G=1\text{A}$ , $di_G/dt=1\text{A}/\mu\text{s}$ | 1      |      |      | $\mu\text{s}$    |
| tg $q$            | $v_J=T_{VJM}$   | 100    |      |      | $\mu\text{s}$    |


## Performance Curves




**Fig1. Power dissipation**



**Fig2. Forward Current Derating Curve**




**Fig3. Transient thermal impedance**




**Fig4. Max Non-Repetitive Forward Surge Current**

**Performance Curves**



**Fig5. Forward Characteristics**



**Fig6. Gate trigger Characteristics**

**Ordering Information :**

| Device         | Packing                   |
|----------------|---------------------------|
| Part Number-BP | Bulk: 8PCS/BOX ;80PCS/CTN |

**\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp.* products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.