



Order Code	A (mm)
705820015	1.5
705820020	2.0
705820025	2.5
705820030	3.0
705820035	3.5
705820040	4.0
705820045	4.5
705820050	5.0
705820055	5.5
705820060	6.0
705820065	6.5
705820070	7.0
705820075	7.5
705820080	8.0
705820085	8.5
705820090	9.0
705820095	9.5
705820100	10.0
705820105	10.5
705820110	11.0
705820115	11.5
705820120	12.0
705820125	12.5
705820130	13.0
705820135	13.5
705820140	14.0
705820145	14.5
705820150	15.0
705820155	15.5
705820160	16.0
705820170	17.0
705820180	18.0

DIM.	TOL
5 mm DOWN	±0,2
5~20 mm	±0,3
20~40 mm	±0,4
40~60 mm	±0,5
60~100 mm	±0,8
100 mm UP	±1,0

Würth Elektronik eiSos GmbH & Co. KG  
EMC & Inductive Solutions

Max-Eyth-Str. 1  
74638 Waldenburg  
Germany  
Tel. +49 79 42 945 - 0

www.we-online.com  
eiSos@we-online.com



CREATED  
D. Fandrey

CHECKED  
S. Klingler

PROJECTION METHOD SCALE 8 : 1

DESCRIPTION  
**AsSLED  
Spacer for 3mm and 5mm LED**

MATERIAL Nylon 66 UL94 V-2, black  
GENERAL TOLERANCE DIN ISO 2768 T1m

ORDER CODE  
705820xxx

WEIGHT STATUS  
Released

REV DATE  
1.0 2015-02-11

PAGE  
DE 1 / 1