

## ATGBICS 3HE00024CA-C network transceiver module Fiber optic 100 Mbit/s SFP 1310 nm

**Brand :** ATGBICS

**Product code:** 3HE00024CA-C

**Product name :** 3HE00024CA-C



Alcatel Compatible Transceiver SFP 100Base-FX 1310nm MMF 2km DOM

[ATGBICS 3HE00024CA-C network transceiver module Fiber optic 100 Mbit/s SFP 1310 nm:](#)

ATGBICS 3HE00024CA 100Base-FX supports a distance of up to 2km over multi-mode fibre (MMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Alcatel 3HE00024CA= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS 3HE00024CA-C. SFP transceiver type: Fiber optic, Maximum data transfer rate: 100 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Width: 12.7 mm, Depth: 55.9 mm, Height: 7.62 mm. Number of products included: 1 pc(s), Package type: Box



Performance		Features	
SFP transceiver type *	Fiber optic	Easy to install	✓
Maximum data transfer rate *	100 Mbit/s	Country of origin	United Kingdom
Interface type *	SFP	Brand compatibility	Alcatel
Single-mode fiber (SMF) supported	✗	<b>Power</b>	
Multi-mode fiber (MMF) supported	✓	Input voltage	3.3 V
Fiber optic connector	LC	Maximum voltage	4 V
SFP transceiver standard	FX	Power consumption (typical)	1.3 W
Maximum transfer distance	2000 m	<b>Operational conditions</b>	
Wavelength	1310 nm	Maximum operating temperature	70 °C
Ethernet LAN	✓	Operating temperature (T-T)	0 - 70 °C
Ethernet interface type	Fast Ethernet	Storage temperature (T-T)	-40 - 85 °C
Copper ethernet cabling technology	100BASE-FX	Operating relative humidity (H-H)	5 - 85%
Digital Diagnostics Monitoring (DDM)	✓	Storage relative humidity (H-H)	5 - 85%
Wavelength-division multiplexing (WDM)	✗	<b>Weight &amp; dimensions</b>	
<b>Features</b>		Width	12.7 mm
Product colour	Silver	Depth	55.9 mm
Housing material	Metal	Height	7.62 mm
Plug and Play	✓	Weight	19 g
Hot-Plug support	✓	<b>Packaging data</b>	
Hot-swap	✓	Number of products included	1 pc(s)
		Package type	Box
		<b>Technical details</b>	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.