



Click [here](#) for the 3D model.

### Dimensions

|    |                  |
|----|------------------|
| D  | 2.29mm +/-0.25mm |
| L  | 4.06mm +/-0.25mm |
| LL | 38.1mm MIN       |
| F  | 0.51mm -0.08mm   |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 200       |

### General Information

|             |  |
|-------------|--|
| Series      | LDD Comm COG   |
| RoHS        | No   |
| Prop 65     | <b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a> . |
| SCIP Number | f30e2214-6f19-489b-928a-4aa9281a81a7   |
| Termination | Lead (SnPb)  |
| AEC-Q200    | No   |
| Notes       | Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk.    |

### Specifications

|                                 |                |
|---------------------------------|----------------|
| Capacitance                     | 1.5 pF         |
| Capacitance Tolerance           | +/-0.5 pF      |
| Voltage DC                      | 200 VDC        |
| Dielectric Withstanding Voltage | 500 VDC        |
| Temperature Range               | -55/+125°C     |
| Temperature Coefficient         | COG            |
| Dissipation Factor              | 0.1% 1 mHz 25C |
| Insulation Resistance           | 100 GOhms      |