



| Specifications | | |
|-----------------------|-----------|-------|
| Description | Value | Unit |
| Technology | Piezo | |
| Resonant Frequency | 4,000 | (Hz) |
| Rated Voltage | 9 | (V) |
| SPL @ 10cm | 80 | (dBA) |
| Capacitance | 9,500 | (pF) |
| Mount Type | Flush | |
| Voltage Range | 1 ~ 25 | (V) |
| Max Rated Current | 7 | (mA) |
| Housing Material | ABS | |
| Operating Temperature | -20 ~ +60 | °C |
| Storage Temperature | -20 ~ +60 | °C |
| Weight | 1 | (g) |

| Notes |
|--|
| 1) All dimensions are in mm unless otherwise noted 2) All parts meet RoHS |



| Revision History | | | | | |
|------------------|---------------------------|------------|------------|-------------|------------|
| Version | Description | Date | Approved | | |
| 1 | Released from Engineering | 10/21/2013 | J.S | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| Drawn by | Date | Checked by | Date | Approved by | Date |
| A.B. | 10/21/2013 | C.E. | 10/21/2013 | J.S | 10/21/2013 |

Piezo Transducer

TP164009-1