

LI0201B241R-12

UNCONTROLLED DOCUMENT

PHYSICAL DIMENSIONS

A 0.80 [0.80]	± 0.08 [0.07]
B 0.50 [0.51]	± 0.08 [0.07]
C 0.50 [0.51]	± 0.08 [0.07]
D 0.41 [0.40]	± 0.08 [0.07]



ELECTRICAL CHARACTERISTICS			
4 W (0.20)	50W (0.2)	Rated Current	
Forward	1.0V		
Reverse	0V		
Maximum	30V	1.00	200 mA




NOTE: UNLESS OTHERWISE SPECIFIED:

1. TAPED AND REELED FOR CURRENT ON SPECIFICATIONS 7 REEL FILLED POLYMER TAPE TAPE
2. MEASUREMENTS SHALL BE MADE IN COMPONENTS SHOULD BE FULLY QUANTITY PREPARED BEFORE TESTING
3. OPERATING TEM. RANGE: -40°C to +125°C (INCLUDING SELF-HEATING)



USE THERMAL SOLDER BRIDGE

RECOMMENDED SOLDER BRIDGE



REVISIONS		APPROVED FOR RELEASE	
NO.	DESCRIPTION	DATE	BY

LI0201B241R-12

0.20 0.2 0.2

1 of 1